

# PlasTEAK®


3489 Sawmill Road Akron, Ohio 44321-0290  
1.800.320.1841 FAX 330.666.0844 www.PlasTEAK.com

## PlasTEAK Vinyl Flooring Trim (Technical Data Sheet)

### Product Description:

**PlasTEAK trim** pieces are available in 3 corresponding colors and sold in 6' pieces.

<u>Item number</u>	<u>Colors:</u>	<u>Available Sizes</u>
M-FLRTRIM1	Fawn	72" x 5/8" x 5/16"
M-FLRTRIM2	Spanish Saddle	72" x 5/8" x 5/16"
M-FLRTRIM3	Almond	72" x 5/8" x 5/16"



### Installation:

On the backside of each trim piece, mark with a pencil the areas that will be bent to border the hatch. Using a heat gun, apply heat to the marked areas and bend to cover the angles of the hatch. At 5" intervals, using stainless steel #4 screws, screw the trim piece to the hatch.

### Storage:

Store products in a clean area protected from the weather on a smooth, flat, dry surface. The installation area, substrate, trim pieces and adhesive must be conditioned at room temperature minimum 68° - 85° F (18° - 29° C) for 48 hours before, during installation and 48 hours after installation for proper acclimatization. It is essential to maintain installation temperatures to prevent adhesive failure and to prevent distortion or destruction of the trim piece(s).

### Maintenance:

Do not clean, rub or apply pressure to the trim pieces for a minimum of 72 hours after the installation is complete to allow for the adhesive to properly cure. After this time the trim pieces can be maintained using a microfiber cloth dampened with diluted pH neutral cleaner and warm water.

### Technical Data:

ASTM F925 – No change

5% Ammonia, 5% Acetic Acid, 70% Isopropyl Alcohol, 5% Sodium Hydroxide, 5% Hydrochloric Acid, Mineral Oil, Bleach, Sulfuric Acid, Kerosene, Olive Oil, 5% Phenol, Gasoline

